

ZW4100A Tracker Light BW4100B Explosion proof Tacker Light




LED



Ex Code: Ex ia IIC T6
Standard: GB3836.1, GB3836.4
IEC60079-11:2006,MOD



Insurance clip



Magnetic base



Arm mounting

Application

It is ideal as a personal indicator to identify the position of workers, it also can serve as signal communication tools in all kinds of hazardous area such as construction, fire fighting, rescue etc.

Characteristics of Performance

- Intrinsically safe type of protection, can be safely used in various flammable and explosive fields (including Zone 0).
- Waterproof & Drop Resistant: Made of PC material, drop resistant to 1 meter.
- Runtime: Powered by two AAA battery. Continuous runtime can exceed 500 hours.
- Flexible&Convenience: Small size, Light weight, easy to operation. It is magnetic, can be attached to the iron surface.
- Ambient Temperature: -60°C-150°C.
- Color Available: The tracker light is available in the following five different colours according to customers requirements: red, blue, yellow, green, white.

Main specification

Specification	Unit	ZW4100A / BW4100B
Rated Voltage	V	3
Current	μ A	<3
Flashing Frequency	Hz	2.7
Max Impulse Current	mA	80
Dimension	mm	70×47×39
Net Weight	Kg	0.1

Drawing of dimension (Dimensions in mm)

