


IP65



Model B

Model A



Application

It is applicable to large and high brightness lighting in the operation sites of large scale construction, rescue and maintenance, accident handling, disaster relieve, etc.

Characteristics of Performance

- The unit can tilt within 300 degrees vertically. The remote control can control the lamp rotation and the light tower on/off within 30 meters.
- The air pump controls extension of the mast.
- The caster wheels and railway wheels on generator set ensure the easy transportation on uneven road.
- The unit is made of high strength metallic materials to ensure the normal operation under various harsh environments and climate. It is IP65, and can stand force 8 wind fresh gale.
- This product is adjustable according to customer's requirements.
- Equipped with control box except the remote control. When the remote control doesn't work or the battery dead, operator can use the control box to control the light tower.

Main specification

Specification		Unit	ZW3500A	ZW3500B	ZW3510A	ZW3510B
Rated Voltage		VAC	220	220	220	220
Lamp	Power of lamp head	W	500×4	500×4	1,000×4	1,000×4
	Light output	lm	10,000×4	10,000×4	20,000×4	20,000×4
	Average service life	h	2,000	2,000	2,000	2,000
Continuous working time	Units once filled oil	h	9-13	9-13	9-13	9-13
High luminance of lamp disc	Minimum height	mm	1,850	1,850	1,850	1,580 or 2,100
	Maximum lifting height		6,300	4,500	6,300	3,500 or 4,500
Generation set	Rated output power/ rated volume of the fuel	W/L	2,000/15	2,000/15	5,000/25	5,000/25
Overall dimension	Length×Width×Height	mm	800×500×750	1,600×500×800	900×550×850	1,600×550×900
Net Weight		Kg	78	78	110	103



Controller



Output sockets



Adjust the angle automatically



Portable



Controlling box (optional)