

IP65

-20°C

+50°C



Application

This product is for use as large area illumination solution on the working sites of large constructions, maintenance, repair, accident spot, and disaster relief etc.

Characteristics of Performance

- The lamp's illuminating angle can be adjusted vertically and horizontally. Its light can cover an area which's radius is 100-150m.
- The lamp is designed to stand harsh vibration. Which solves the bulb and bracket break problem.
- The air pump controls extension of the mast. The remote control can control the on/off of the light tower within 30meters.
- The caster wheels and railway wheels on generator set ensure the easily transportation on uneven road.
- The unit is made of high strength metallic materials to ensure the normal operation under various harsh environments and climate. It is IP65, and can stand force 8 wind fresh gale.
- This product is adjustable according to customer's requirements.

Main specification

Specification		Unit	ZW3500C	ZW3510C	
Rated voltage		VAC	220	220	
Lamp panel	Power		W	400×2	1000×2
	HPS discharge lamp	Light output	lm	48000×2	140000×2
		Lamp useful time	h	25000	28500
	MH discharge lamp	Light output	lm	36000×2	105000×2
Lamp useful time		h	9000	9000	
Continuous operation time		h	13	13	
Cylinder	Smallest rise height		mm	1750	1750
	Highest rise height		mm	3500	3500
Generator	Rated output power/ rated capacity of fuel oil		W/L	2000 / 15	5000 / 25
Dimension	length×width×height		mm	1500×500×800	1500×500×800
Weight		Kg	72	112	



Illuminate Angle adjustable



Controller