

ZW7600 Railway LED Signal Flashlight



LED

IP65

-20 °C

+50 °C



Three-colour



Tail light



Portable



Charger

Application

It is used at railway, aviation and other transportation area and some special fields, serving as signal indication, safety warning and normal illumination.

Characteristics of Performance

- It uses CREE LED light source, with 100,000hours service life. The reflector adopts hi-tech surface finishing technology, make sure a high light reflectivity. The effective beam range can exceed 100 meters. Any two of the red, yellow, green light can be chosen as signal light. Its colored signal light's beam distance can reach 5,000meters.
- It is sealed to IP65 preventing the ingress of water; The housing is made of PC material, drop resistant to 1 meter. It can withstand high and low temperature suitable to be used in all kinds of harsh environment.
- The rear light on its tail is ideal as a personal indicator to identify the position of the users. It eliminates the danger and ensure the user's safety in the dark.
- Use of the latest large bulk capacity lithium-iron battery with long service life improves reliability and eliminates 'memory' affect.
- Easy to carry.

Main specification

Specification	Unit	ZW7600	
Rated voltage	V	3.7	
Rated capacity	mAh	4,400	
Current	White Worklight	380	
	Signal light	120	
	Real light on the tail	20	
Light Output		lm	170
Runtime	White worklight	h	≥10
	Signal light	h	≥30
Recharging time		h	12
Service Life		h	100,000
Battery Recharge Cycle		Times	≈1000
Dimension	External diameter	mm	φ 66
	Length		172
Net weight		g	265

Drawing of dimension (Dimensions in mm)

