

Application

This product is widely applicable to the illumination for the stations, large factories, supermarkets, warehouses and stadiums as high bay light.

Characteristics of performance

- High efficient famous light source with reliable performance ensures 20% brighter illumination than light source of other brand.
- Reflector is made of import material. High reflecting effect, ideal for all kinds high bay for fixed illumination.
- Unique structure design and light weight material for great dust-proof, water-proof, corrosion resistance and anti rust.
- The electrical cabinet has good heat radiation, and can radiate the heat produced from the bulb and ballast rapidly, and prevent the electric fittings from damaging due to the high temperature in the ballast box.
- Derrick hanging, chain installation, safety is simple and convenient.

Main specification

Input Voltage	AC220V 50Hz (60Hz Optional)
Ingress Protection	IP65
Anti Corrosion Grade	WF2
Insulation Grade	I
Space Height Ratio	1.5
Leading-in cable diameter	φ 8mm - φ 10mm
Dimension	φ 545 × 698mm
Net Weight	13.6Kg

IP65

-40°C


+50°C



E40



Light distribution curve



Ordering reference

Ordering Reference	Light Source	Wattage (W)	Luminous flux (lm)	Lamp Average Life (h)
ZY8521-J1000	MH	1,000	105,000	12,000

Drawing of dimension (Dimensions in mm)

